Jeep Wrangler JK 2007-2018

		U					
Lift Height	Stock	2.5" Lift		3.5" Lift		4.5" Lift	
Vehicle Type		2 Door		2 Door		2 Door	
Suspension Component	Decimal	Decimal	Fraction*	Decimal	Fraction*	Decimal	Fraction*
Front Lower Control Arms	22.621	22.881	22-7/8"	23.055	23-1/16"	23.269	23-1/4"
Front Upper Control Arms	18.773	18.795	18-13/16"	18.908	18-7/8"	19.074	19-1/16"
Rear Lower Control Arms	19.764	20.000	20"	20.000	20"	20.000	20"
Rear Upper Control Arms	17.421	18.125	18-1/8"	18.125	18-1/8"	18.125	18-1/8"
Front Track Bar	32.383	32.647	32-5/8"	32.796	32-13/16"	32.974	33"
Rear Track Bar w/Bracket	40.090	40.023	40-1/16"	40.119	40-1/8"	40.119	40-1/8"
Lift Height		2.5" Lift		3.5" Lift		4.5" Lift	
Vehicle Type		4 Door		4 Door		4 Door	
Front Lower Control Arms	22.621	22.881	22-7/8"	23.055	23-1/16"	23.269	23-1/4"
Front Upper Control Arms	18.773	18.795	18-13/16"	18.908	18-7/8"	19.074	19-1/16"
Rear Lower Control Arms	19.764	20.000	20"	20.000	20"	20.000	20"
Rear Upper Control Arms	17.421	17.750	17-3/4"	17.750	17-3/4"	17.750	17-3/4"
Front Track Bar	32.383	32.647	32-5/8"	32.796	32-13/16"	32.974	33"
Rear Track Bar	40.090	40.023	40-1/16"	40.119	40-1/8"	40.119	40-1/8"

NOTE : These are helpful starting specs. These are NOT intended as final measurements. Due to many variables, final adjustments should be made once all components are installed, then fine tune for your specific vehicle. Make sure to stay within the max lengths shown below.

OVERLAND PLUS	MIN	MAX			
COR-1708100	22-1/2"	24-1/8"	NOTE: Adjuster frame side.		
COR-1708101	18-1/16"	19-1/2"	NOTE: Adjuster frame side.		
COR-1709102	19-7/16"	21-1/8"	NOTE: Adjuster frame side.		
COR-1709103	17-5/16	18-11/16"	NOTE: Adjuster either side.		
PREMIUM					
COR-1808100	22-3/4"	23-9/16"	NOTE: Adjuster frame side.		
COR-1808101	18-1/4"	21-5/16"			
COR-1809102	19-11/16"	20-9/16"	NOTE: Adjuster frame side.		
COR-1809103	17-5/16"	18-11/16"	NOTE: Adjuster either side.		
TRACK BARS					
COR-4508100	32"	34-7/16"	NOTE: Adjuster axle side.		
COR-4508110	39-7/8"	41-3/4"	NOTE: Adjuster frame side.		
	Torque spec		Wrench size		
1-14 Grade 5 Hex Jam Nut	398 f	t/lbs.	1-1/2"		
1-1/4-12 Grade 5 Hex Jam Nut	723 f	t/lbs.	1-7/8"		

Recommended caster for all models and heights should be around 4-6 degrees of caster.

Actual decimals have been converted to the nearest fraction.

NOTE: Full instructions available online! These are helpful starting points or a quick guide to assist in your installation.